

DT, KDT, DTLF SERIES OIL-FREE COMPRESSORS

Becker 100% Oil-Free Rotary Carbon Vane Compressors

Becker oil-free compressors are designed to operate on a continuous duty basis at any pressure level from open flow to 26 PSIG, depending on the series. All Becker oil-free pumps utilize self-lubricating, graphite composite vanes, specifically engineered for Becker Pumps. No oil to change and only minimal maintenance is required. Each pump comes with a built-in inlet filter, pressure relief valve and vibration isolators as standard equipment.

DT SERIES					
Model	Horsepower	CFM @ Open Flow	Max. Pressure (PSIG)	Noise Level (dBa)	
DT 4.4	0.24	2.9	15	60.5	
DT 4.8	0.6	5.6	15	61.5	
DT 4.10	0.6	7.1	15	62	
DT 4.16	0.94	11.2	15	64	
DT 4.25	1.75	17.6	15	67	
DT 4.40	2.95	28	15	70	



KDT SERIES					
Model	Horsepower	CFM @ Open Flow	Max. Pressure (PSIG)	Noise Level (dBa)	
KDT 3.60	5	37	22	74	
KDT 3.80	7.5	45	22	76	
KDT 3.100	10	69	22	78	
KDT 3.140	12	90	22	84	

DTLF SERIES



Contraction of the second	

FEATURES

DTLF 2.200

DTLF 2.250

DTLF 2.400

DTLF 2.500

15 - 17.7

15 - 24.1

20 - 30

25 - 48.3

127

172

259

353

- 100% oil-free
- Continuous duty rated
- Quiet operation
 - Compact design
- Low maintenance

BENEFITS

7.25 - 26.1

7.25 - 26.1

13.1 - 26.1

11.6 - 26.1

- No oil or water
- No cycling times
- No silencer enclosures needed
- Small footprint for space savings
- Field serviceable reduces downtime

82

85

81

82

APPLICATIONS

- Soil remediation
- Aeration
- Waste water treatment
- Pneumatic conveying
- Printing

Contact our staff today. We're ready to help. Call 888-633-1083 or email: info@beckerpumps.com.



Nationwide Sales and Service: USA, Canada, and Mexico 888-633-1083

Becker Pumps Corp. • 100 East Ascot Lane • Cuyahoga Falls, Ohio 44223 Tel 330-928-9966 • Fax 330-928-7065 • info@beckerpumps.com • www.beckerpumps.com