VT, KVT, VTLF SERIES

# **OIL-FREE VACUUM PUMPS**



## **Becker 100% Oil-Free Rotary Carbon Vane Vacuum Pumps**

Becker oil-free vacuum pumps are designed to operate on a continuous duty basis at any vacuum level from open flow to 27" Hg., depending on the series. All Becker oil-free pumps utilize self-lubricating, graphite composite vanes, specifically engineered for Becker pumps. No oil to change and only minimal maintenance is required. Each pump comes with a built-in inlet filter, vacuum relief valve and vibration isolators as standard equipment.

VT Series						
Model	Horsepower	CFM @ Open Flow	Max. Vacuum (Inches Hg)	Noise Level (dBa)		
VT 4.4	0.289	2.8	25	61		
VT 4.8	0.59	5.4	25	61		
VT 4.10	0.6	7.1	25	62		
VT 4.16	0.94	11	25	64		
VT 4.25	1.2	17.7	25	67		
VT 4.40	2.0	28	25	72		



KVT Series						
Model	Horsepower	CFM @ Open Flow	Max. Vacuum (Inches Hg)	Noise Level (dBa)		
KVT 3.60	3	39	27	73		
KVT 3.80	5	46	27	75		
KVT 3.100	5	66	27	77		
KVT 3.140	7.5	91	24	79		



VTLF Series						
Model	Horsepower	CFM @ Open Flow	Max. Vacuum (Inches Hg)	Noise Level (dBa)		
VTLF 2.200	7.5	128	24	77		
VTLF 2.250	8.9	169	24	79		
VTLF 2.250 SK	10	174	27	79		
VTLF 2.400	15	270	24	79		
VTLF 2.500	25	336	22	80		



#### **Features**

- 100% oil-free
- Continuous duty rated
- Quiet operation
- Compact design
- Low maintenance

#### **Benefits**

- No oil or water
- No cycling times
- No silencer enclosures needed
- Small footprint for space savings
- Field serviceable reduces downtime

### **Applications**

- Medical/surgical
- Packaging
- Robotics/pick and place
- Material handling
- Vacuum hold down
- Printing

We are Ready to Help! Sales and Service for USA, Canada, and Mexico

Call 888-633-1083 or go to www.beckerpumps.com

100 East Ascot Lane • Cuyahoga Falls, Ohio 44223



Order Becker Genuine Parts
Online 24/7
www.beckerpumps.com/shop