



U Series Rotary Vane Oil-Lubricated Vacuum Pumps

The Becker U series pumps are cool running, quiet, and highly efficient. Providing vacuum to 0.075 Torr, our compact, direct-drive, oil-flooded pumps offer the fastest pump downtime in the industry. This ensures greater product output. Our dual stage oil separation system is 99.9+% efficient. No matter what equipment you have, Becker has the pump solution for you.

MAKE IT TRANSFORM

MAKE IT BECKER



Benefits

- Faster pump downtime increases production
- High efficiency oil separator element
- High efficiency cooling
- Most efficient IE3 motors in the industry

	U 4.20		U 4.40		U 5.71		U 5.101		U 5.166		U 5.201		U 5.301	
	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz
Nominal Air Flow (CFM)	10.6	12.4	24	28	41.2	49.4	58.9	70.6	97.0	116	118	141	176	211
Maximum Vacuum (Torr)	1.0		0.375		0.075		0.075		0.075		0.075		0.075	
Horsepower	1.2		2.4		2.4		3.5		4.8* or 6.4		6.4* or 8.9		8.9* or 12	
Inlet Size (Inches)	0.75		1.0		1.25		1.25		2.0		2.0		2.0	

**Primary Packaging version for drawing deeper than 685 Torr (27" Hg.)*

	U 4.400 SA/K		U 4.400 F/K		U 4.630 SA/K		U 4.630 F/K	
	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz
Nominal Air Flow (CFM)	256	299	256	299	366	430	366	430
Maximum Vacuum (Torr)	2		0.5		2		0.5	
Horsepower	15		15		25		25	
Inlet Size (Inches)	3		3		3		3	

We are Ready to Help! Sales and Service for USA, Canada, and Mexico

Call 888-633-1083 or go to www.beckerpumps.com

100 East Ascot Lane • Cuyahoga Falls, Ohio 44223



Order Becker Genuine Parts

Online 24/7

www.beckerpumps.com/shop