SE100C—SE300C

SEXTUPLEX HOOK & CLAW MEDICAL VACUUM SYSTEM

MAKE IT BECKER.

figure TE250D system

MODEL	HP	END VACUUM ("Hg)	OPEN FLOW (SCFM)	FLOW @ 19"HG (SCFM)	BTU/HR (19"Hg)	BTU/HR (MAX VAC)	FLA (Per Pump)			SOUND [1] dB(A)
							208	230	460	
SE100C	4	28.1	323.7	98.7	47,770	51,182	10.8	10	5.01	71
SE150C	5.4	26.6	485.6	148.3	70,392	72,099	14.6	13.5	6.75	71
SE300C	10	25.1	912.3	299.2	127,614	127,614	26.2	24.8	12.4	72

(1) Per Pump dB(A) – According to DIN EN ISO 3744 (KpA = 3db(A)), 39.4 inch distance, at medium load, both connection sides piped
(2) All values listed are at 60Hz
(3) Reference data (atmosphere) 0"HgV,68°F; Tolerance: ±5%
(4) Values listed per NFPA standard with one pump as reserve

BECKER

THE BECKER ADVANTAGE SYSTEM

FEATURES OF THE SEXTUPLEX HOOK & CLAW

Medical Vacuum System

BECKER ADVANTAGE C SEXTUPLEX EXPANDABLE VACUUM SYSTEM

Pneumatic vacuum system designed for medical use. Features six Becker brand vacuum pumps, with integrated filtration and safety relief valves. Pumps, air receiver and control panel are mounted to modular skids to allow for future expansion of up to six pumps. All medical systems are NFPA 99 compliant and include all necessary redundancies. All systems are tested for leaks and functionality before shipping.

The Advantage C sextuplex systems include:

- Six Becker Hook & Claw vacuum pumps
- AMSE coded vacuum receiver with drain and bypass manifold
- Single point service for electrical and vacuum connections
- Integrated electrical panel with expandable system controls
- Optional external filtration canisters (one per pump)

VACUUM PUMPS

All pumps used on our systems are Becker Manufactured and individually tested at factory before shipping. Becker hook and claw vacuum pumps feature an oil-less/touch-less working chamber. Additional specifications are:

- End vacuum of 25-28"Hg (Model Dependent)
- Integrated 2-micron paper inlet filter
- Vacuum relief valve and anti-return valve
- Integrated exhaust silencer box
- Gear Oil sight glass for visual inspection
- Liquid filled vacuum gauges installed at the pump
- Low maintenance requirements
- Single shaft direct drive through coupling
- IE3/NEMA PREMIUM efficiency motors
- TEFC Motors
- 208V/230V/460V/575V – 3-phase motor options

PLUMBING & RECEIVER

All vacuum pumps are plumbed to a manifold and connected to the air receiver. Check valves are installed at each pump inlet to prevent backflow in the system. Ball valves installed for pump and receiver isolation. One point connection for vacuum plumbing is standard for all Becker systems. Optional manifold and one point connection for exhaust plumbing is available.

All air receivers are ASME stamped to code and may have a mounted bypass and drain to allow for manual liquid removal.

CONTROL PANEL

NEMA type 3R, 4 & 12 enclosure with UL listing; mounted and prewired for expandable system controls. Expandable system panels are designed to allow easy installation of additional pump modules in the event new pumps are added to the original system (6 pump max per system). Becker expandable system controls are designed with lead/lag sequencing to maintain the desired vacuum range and provide automatic alternation of vacuum pumps to maintain equal run time between available pumps. Each system has adjustable minimum and maximum run timers to facilitate the correct activation of pumps in the system. Additional elements included are:

- Redundant Transformers per NFPA 99
- 115V low voltage control transformer with fused primary and secondary
- Motor starters with overload protection
- Automatic low voltage transformer switching with alarm
- One Hand-Off-Auto switch per pump
- System run & alarm lamps
- Sound horn for notification of system alarms
- Silence/acknowledge alarm push button
- CVT failure lamp alert
- Isolated relays for remote alarm installation
- Preinstalled vacuum transducer

Panel also includes a 7" touchscreen LCD HMI unit to display system status. HMI provides access to basic system setup settings such as number of active pumps, vacuum high/low setpoints, and min/max run time. Live monitoring of each pump motor's average amperage and amperage per phase is also available.

PLC control unit offers the following communication services:

- Ethernet/IP slave device
- Modbus TCP
- SMS/email notifications
- Web server (WebVisu)

DIMENSIONS

MODEL	LENGTH (Inches)	WIDTH (Inches)	HEIGHT (Inches)	RECEIVER CAPACITY (Gallons)	INLET/ EXHAUST (Inches)	WEIGHT (Pounds)
SE100C	90	58	98	120	2	5,530
SE150C	102	70	108	240	3	6,425
SE300C	102	70	110	240	3	9,250

Dimensions subject to change.
Minimum clearance around system is 36 inches.
Contact factory for dimensional drawings.